

产品信息 Product Information

SJ607-R900



项目/Project		参数
轴数/Degree of the freedom		6
运行半径/Working radius		905MM
最大负载/Maximum load		7KG
额定负载/Rated load		5KG
工作范围 Working range	轴1/Axis1	-170°/+170°
	轴2/Axis2	-130°/+100°
	轴3/Axis3	-50°/+200°
	轴4/Axis4	-160°/+160°
	轴5/Axis5	-130°/+130°
	轴5/Axis5	-180°/+180°
重复定位精准度 Position repeatability		±0.05MM
机身材质 fuselage material		铸件 casting
本体重量/Body weight		51KG
输入电压/Input voltage		220V
动力装置/Power plant		直流伺服电机 DC Servo Motor
减速装置/Reduction gear		谐波减速 Harmonic deceleration
环境要求 Environmental requirements	温度/Temperature	5°C-50°C
	湿度/Humidity	10%-80%
安装方式/Installation		台面、侧装、倒装 Table top, side mount, flip mount
最大速度 Maximum speed	轴1/Axis1	148°/SEC
	轴2/Axis2	148°/SEC
	轴3/Axis3	178°/SEC
	轴4/Axis4	166°/SEC
	轴5/Axis5	178°/SEC
	轴6/Axis6	225°/SEC



